



TURFACE® QuickDry®

After a rain, Turface® QuickDry® makes muddy, slippery conditions a thing of the past. QuickDry will not cake, become slippery or leave an infield rock-hard upon drying. It features easy application as a topdressing during and after rains. Just apply QuickDry to wet areas or puddles, let the product begin to absorb the moisture, and rake the area to return to play time and time again. There is a reason Quick Dry is called the Game Saver!

MANUFACTURER: PROFILE Products LLC
750 Lake Cook Road, Suite 440, Buffalo Grove, IL, 60089
1 800 207 6457



1. Materials: A calcined, non-swelling illite and silica clay.
2. pH range: 5.5 ± 1.0
3. CEC: 33.6 mEq/100g
4. Particle Stability: Sulfate Soundness testing (ASTM C-88) and static degradation test not to exceed 4% loss over 20 years
5. Bulk Density: $38 \pm 3 \text{ lb./ft}^3$
6. Color Range: Reddish/Tan
7. Packaging: 50 pound valve bags

Quick Dry® SIEVE ANALYSIS:
80% minus 30 Mesh

PRODUCT DESCRIPTION: Must be an illite silica blend at 40% minimum and 60% minimum amorphous silica. Material must be processed in a rotary kiln operation at temperatures not less than 1200 degrees Fahrenheit. Product must then be screened and de-dusted.

INSTALLATION: Pour TURFACE Quick Dry directly into puddles on the infield. Allow Quick Dry to absorb the standing water. Rake the area and smooth Quick Dry into the infield.

CHEMICAL DESCRIPTION:

SiO₂ - 74.0%
Al₂O₃ - 11.0%
Fe₂O₃ - 5.0%

All other chemicals equal less than 5% and include :
CaO, MgO, K₂O, Na₂O and TiO₂

