

#### TURFACE® MVP®

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier: Common Name: SDS Number: Revision Date:	TURFACE® MVP® N.A. BLM001 4/19/2023
Supplier Details:	PROFILE Products, LLC 750 LAKE COOK ROAD, SUITE 440 BUFFALO GROVE, IL 60089
Contact: Phone: Fax: Email: Internet:	ChemTrec Acct #: CCN792719 (847) 215-1144 (847) 215-0577 tech@profileproducts.com www.profileproducts.com
Emergency:	Emergency Phone: (800) 424-9300 (ChemTrec)

Description: Heat Treated Montmorillonite Clay Mineral.

## HAZARDS IDENTIFICATION

### **Classification of Substance**

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Specific target organ toxicity - Single exposure, 3

### **GHS Label Elements, Including Precautionary Statements**

### GHS Signal Word: WARNING

### **GHS Hazard Pictograms:**



#### **GHS Hazard Statements:**

H335 - May cause respiratory irritation

#### **GHS Precautionary Statements:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust.

# Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Inhalation:	Lungs
Skin Contact:	Wash with soap and water until clean.
Eye Contact:	Wash out with water.
Ingestion:	No adverse effect.

Crystalline Silica (Quartz) [EPA Hazard Category: Health]

## Carcinogen: OSHA - No NTP - Yes (respirable) IARC - Yes

This product contains up to 5% crystalline silica. The International Agency for Research on Cancer (IARC) has stated that there is sufficient evidence of carcinogenicity of crystalline silica to human beings. It was noted that carcinogenicity was not detected in all industrial circumstances studied. The NTP's Sixth Annual Report on Carcinogens include respirable crystalline silica. The Hazard Communication Standard (29CFR 1910.1200) requires that any material containing over 0.1% of a substance reported as a carcinogen in an IARC monograph or the most recent NTP Annual Report on Carcinogens must be identified as a carcinogen. These identifications are for hazard communications only and do not serve as assessments of

carcinogenic risk. Crystalline silica is known to cause silicosis. At dust levels below the recommended PEL exposure to the crystalline silica contained in this product should not present a health hazard.

Inhalation of excessive concentrations of any dust, including this material, may lead to lung injury. As formulated, this product is not expected to form appreciable respirable crystalline silica dust from use or attrition. Because application and exposure data indicate exposure to respirable quartz in the normal use of the ingredient within this product which contains crystalline silica, is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV). Adverse effects would not be expected from normal use of this product

## COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:				
CAS#	%	Chemical Name:		
14808607	3-5%	Silica, crystalline quartz		

FIRST AID MEASURES
Inhalation: Move to fresh air.

Skin Contact:Wash throughly with soap and water.Eye Contact:Flush thoroughly with water. See a physician if discomfort persists.Ingestion:None. If large quantities are ingested consult your physician.

## FIRE FIGHTING MEASURES

Non-flammable and non-hazardous

## 6 ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.

7	HANDLING AND STORAGE		
Handling Precautions:	Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.		
Storage Requirements:	Store in drv area.		

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
Personal Protective Equipment:	Respiratory Protection: If dust concentrations exceed recommended Permissible Exposure Limits, use NIOSH- approved dust respirators, with approval TC-21C-xxx, until feasible engineering controls are completed.
	Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than
	Permissible Exposure Limits is recommended.
	Eye Protection: If high dust concentrations exist, tight-fitting goggles are recommended to reduce dust
	exposure to the eyes.
	Other Protective Equipment: Optional.
Exposure Limits (respir	able fraction) in Air:
OSHA & MSHA - PEL	10mg/m3
	% SiO2 + 2 (8-Hour TWA)
ACGIH - TLV	0.05 mg/cubic meter (8-Hour TWA)
NIOSH	0.05mg/cubic meter (10-Hour TWA, 40-hour work week)

Exposure Limits refer to the respirable fraction.

PEL means OSHA Permissible Exposure Limit.

TLV means American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value.

MSHA means Mine Safety and Health Administration Exposure Limit.

TWA means 8 hour Time Weighted Average.

## PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Physical State: Vapor Pressure: Brown to buff-colored granular particles Solid granular particles. N.A.

Odor:	Negligible
Solubility:	Negligible
Freezing/Melting Pt.:	N.A.
Bulk Density:	37 lbs/cubic ft.

# STABILITY AND REACTIVITY

Chemical Stability: Materials to Avoid: Hazardous Decomposition: Hazardous Polymerization: Turface is stable under all normal conditions. Unreacted polymer monomers None known. Will not occur.

# TOXICOLOGICAL INFORMATION

Inhalation- N.E. Intravenous- Rat - LD50:15mg/kg Oral - Rat - LD50:3160 mg/kg

# 12 ECOLOGICAL INFORMATION

Naturally occuring, inorganic, crystalline, absorbent, clay minerals, such as Attapulgalite and Montmorillonite, are used in a wide variety of commercial, industrial, and consumer applications. Calcium bentonite and sodium bentonite clays, which are composed mostly of monmorillonite, have been listed for many years as Generally Recognized as Safe (GRAS) by the U.S. Food and Drug Administration (FDA) for use in human food and animal feed.

## 3 DISPOSAL CONSIDERATIONS

Can be disposed of in an approved disposal facility, in accordance with applicable federal, state, and local regulations. The nature and extent of contamination, if any, may require use of specialized disposal methods.

TRANSPORT INFORMATION
REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Silica, crystalline quartz (14808607) [3-5%] MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory CODE Descriptions MASS = MA Massachusetts Hazardous Substances List NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level COMPONENT / (CAS/PERC) / CODES

\*Silica, crystalline quartz (14808607 3-5%) MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS MASS = MA Massachusetts Hazardous Substances List NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level

TSCA = Toxic Substances Control Act

## 16 OTHER INFORMATION

### **Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Revision Date: 4/19/2023