

GHS Safety Data Sheet PROFILE Products, LLC

Field & Fairway® Emerald

MSDS Number: BLM019

Revision Date: 5/15/2015 Page 1 of 6

PRODUCT AND COMPANY IDENTIFICATION

SDS

Manufacturer

PROFILE Products, LLC 750 LAKE COOK ROAD SUITE 440 BUFFALO GROVE, IL 60089

Phone:	(847) 215-1144
Fax:	(847) 215-0577
Email:	profileproducts.com
Web:	profileproducts.com www.profileproducts.com

Product Name:Field & Fairway® EmeraldRevision Date:5/15/2015MSDS Number:BLM019Common Name:N.A.CAS Number:70892-59-0

Description: Calcined, non-swelling illite and non-crystalline opal CT mineral.

2	HAZARDS IDENTIFICATION
Inhalation:	Lungs
Skin Contact:	No
Ingestion:	No
NFPA:	Health = 1, Fire = 0, Reactivity = 0







SDS

MSDS Number: BLM019

 Revision Date:
 5/15/2015

 Page
 2
 of
 6

GHS Signal Word: WARNING

GHS Hazard Pictograms:



GHS Classifications: Health, Specific target organ toxicity - Single exposure, 3

GHS Phrases: H335 - May cause respiratory irritation

GHS Precautionary Statements:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Crystalline Silica (Quartz) [EPA Hazard Category: Health]

Carcinogen: OSHA - No NTP - Yes (respirable) IARC - Yes

This product contains up to 5% crystalline silica. The International Agency for Research on Cancer (IARC) has stated that there is sufficient evidence of carcinogenicity of crystalline silica to human beings. It was noted that carcinogenicity was not detected in all industrial circumstances studied. The NTP's Sixth Annual Report on Carcinogens include respirable crystalline silica. The Hazard Communication Standard (29CFR 1910.1200) requires that any material containing over 0.1% of a substance reported as a carcinogen in an IARC monograph or the most recent NTP Annual Report on Carcinogens must be identified as a carcinogen. These identifications are for hazard communications only and do not serve as assessments of carcinogenic risk. Crystalline silica is known to cause silicosis. At dust levels below the recommended PEL exposure to the crystalline silica contained in this product should not present a health hazard.

Inhalation of excessive concentrations of any dust, including this material, may lead to lung injury. As formulated, this product is not expected to form appreciable respirable crystalline silica dust from use or attrition. Because application and exposure data indicate exposure to respirable quartz in the normal use of the ingredient within this product which contains crystalline silica, is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV). Adverse effects would not be expected from normal use of this product

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name
14808607	3-5%	Silica, crystalline quartz
26172554	<.005%	3(2H)-Isothiazolone, 5-chloro-2-methyl-
2682204	<.005%	3(2H)-Isothiazolone, 2-methyl-
57556	<.06%	Propylene glycol
63148629	<.005%	Siloxanes and Silicones, di-Me





SDS

MSDS Number: BLM019

Revision Date: 5/15/2015 Page 3 of 6

4	FIRST AID MEASURES	
Skin Contact:	Wash throughly with soap and water.	
Eye Contact:	Flush thoroughly with water. See a physician if discomfort persists.	

FIRE FIGHTING MEASURES	
------------------------	--

Non-flammable and non-hazardous

|--|

Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.

7	HANDLING AND STORAGE
Handling Precautions:	Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.
Storage Requirements:	Store in dry area.





Revision Date: 5/15/2015

Page 4 of 6

MSDS Number: BLM019

EXPOSURE CONTROLS/PERSONAL PROTECTION

SDS

Personal Protective Equip: Respiratory Protection: If dust concentrations exceed recommended Permissible Exposure Limits, use NIOSH- approved dust respirators, with approval TC-21C-xxx, until feasible engineering controls are completed. Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than Permissible Exposure Limits is recommended. Eye Protection: If high dust concentrations exist, tight-fitting goggles are recommended to reduce dust exposure to the eyes. Other Protective Equipment: Optional. Exposure Limits (respirable fraction) in Air: **OSHA & MSHA - PEL** 10mg/m3 % SiO2 + 2 (8-Hour TWA) ACGIH - TLV 0.05 mg/cubic meter (8-Hour TWA) NIOSH 0.05mg/cubic meter (10-Hour TWA, 40-hour work week)

Exposure Limits refer to the respirable fraction.

PEL means OSHA Permissible Exposure Limit.

N.A.

TLV means American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value. MSHA means Mine Safety and Health Administration Exposure Limit.

TWA means 8 hour Time Weighted Average.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Vapor Pressure: Green granular particles

Odor: Solubility: Freezing/Melting Pt.: N.A. **Bulk Density:**

Negligible Negligible 40 lbs/cubic ft.

STABILITY AND REACTIVITY

Stability: Materials to Avoid: Hazardous Polymerization:

Field & Fairway Emerald is stable under all normal conditions. Unreacted polymer monomers Will not occur.

TOXICOLOGICAL INFORMATION

Inhalation- N.E. Intravenous- Rat - LD50:15mg/kg Oral - Rat - LD50:3160 mg/kg



GHS Safety Data Sheet PROFILE Products, LLC

Field & Fairway® Emerald

MSDS Number: BLM019

Revision Date: 5/15/2015

Page 5 of 6

ECOLOGICAL INFORMATION

SDS

13 DISPOSAL CONSIDERATIONS

Can be disposed of in an approved disposal facility, in accordance with applicable federal, state, and local regulations. The nature and extent of contamination, if any, may require use of specialized disposal methods.

14	TRANSPORT INFORMATION

DOT Class: Not regulated #





MSDS Number: BLM019

Revision Date: 5/15/2015

Page 6 of 6

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

SDS

*Silica, crystalline quartz (14808607 3-5%) MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

*3(2H)-Isothiazolone, 5-chloro-2-methyl- (26172554 <.005%) TSCA

*3(2H)-Isothiazolone, 2-methyl- (2682204 <.005%) TSCA

*Propylene glycol (57556 <.06%) HAP, PA, TSCA

*Siloxanes and Silicones, di-Me (63148629 <.005%) TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TXAIR = TX Air Contaminants with Health Effects Screening Level

TSCA = Toxic Substances Control Act

HAP = Hazardous Air Pollutants

16	OTHER INFORMATION
----	-------------------

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).